

## MVP9-A4-R

ViewPro 

### 4M HD IP WDR/TDN In/Outdoor IR Fixed Dome Camera



### FUNCTIONS

#### Optimized Multiple Profile Streaming

Optimized Multiple Profile Streaming Up to 4 streams are able to be set by different setting parameters such as res. video rate and frame rate to be serviced for different purposes at 1080p environments.

#### ROI (Region of Interest)

ROI (Region of Interest) Gives efficient video rates with optimized video quality. Frequently moving areas are keeping much better quality. On the other hands, less moving areas are dropping video rates.

#### Smart AVC

Smart AVC The "Advanced Video Coding" provides the most efficient way to stream audio & video data through network even 1080p at 600kbps bandwidth.

#### Advanced built in ISP

Advanced built in ISP 3D-DNR, Adjustable 3A features, Defect Pixel Correction, WDR, HDR, lens correction and even more advanced ISP functions are provided from built in ISP.

#### Two Motor MFZ (Motorized Focus Controllable) / P-Iris lens

Two motor MFZ(Motorized Focus Controllable) / P-Iris lens Focus control algorithm by SW enables to control two motors motorized lens remotely with the most cost-performance way. P-Iris gives the clearest focus by enabling automatic and precise control of iris opening. It delivers high resolution images with good depth of field.

#### Fluid Integration Way



Fluid integration way The latest Onvif profiles(S,G,Q) are optimized to have interoperability with any kind of purpose. Well-structured CGI-API plug in gives even more detailed functions to be integrated to VMS.

### SYSTEM OVERVIEW

ViewPro HD IP series network camera supports some intelligent functions, such as perimeter protection and smart motion detection. It adopts starlight solution, which makes a better image effect in low illuminance.

### FEATURES

- 1/3" 4.0M CMOS
- Outputs max. 4.0M (2560 x 1440)@30fps
- Focus Length: 2.8-12mm F1.4
- Video Compression: H.264, MJPEG
- Streaming Performance: 2560x1440/30 + 800x600/30 + 480p/30 + 1-pass lens correction
- 100Kbps ~ 10Mbps, Multi-rate for Preview and Recording
- Body Material: Aluminum Die-casting
- Advanced built in ISP
- Real-time High Definition Camera
- Fluid integration way
- Dimensions (D x H): Ø125 x 92 mm



# MVP9-A4-R

# ViewPro

## TECHNICAL SPECIFICATION

### CAMERA

Image Sensor	1/3" 4.0M CMOS
Total Pixels	2688(H) X 1520(V)
Focal Length	2.8-12mm F1.4
Lens Type	Two Motor MFZ (Motorized Focus Zoom) AF
IRIS Type	Precise-iris
Field Angle (FOV)	D:100°~37°, H:87°~32°, V:47°~18°
Shutter Speed	Auto / Manual (1/30 ~ 1/32000), Anti-Flicker, Slow Shutter (1~1/5, 1/7.5, 1/10)
Min. Illumination	0.2 Lux, 0 Lux with IR (F1.4)
IR LEDES	H2IR
IR Distance	70ft (21.34m)
Dynamic Range Conf.	WDR (2x,3x)
Dynamic Range	120dB or above
S/N Ratio	50dB
Pan / Tilt / Zoom	Z: X4.2 Optical
Day & Night	TDN (True Day & Night)
DNR	3D-DNR
Privacy Mask Support	16 Programmable Zone
AGC	Auto
Other Image Processing	Configurable Exposure, White Balance, Sharpness

### ENCODER (Audio & Video)

Video Compression	H.264, MJPEG
H.264 Profile	BP / MP / HP
Max Resolution	2560 x 1440
Multiple Profile Streaming Performance	2560x1440/30 + 800x600/30 + 480p/30 + 1-pass lens correction
Video Bitrate	100kbps~10Mbps, Multi-rate for Preview and Recording
Bitrate Control	Multi Streaming CBR/VBR at H.264 (Controllable frame rate and Bandwidth)
Audio Compression	-
Edge Storage	Micro SD / SDHC / SDXC
Special Feature	Smart LBR, ROI

## SECURITY & NETWORK

Network Protocol	IPv4/IPv6, Zero config (Auto IP) ONVIF, TCP/IP, UDP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2c/v3 (MIB-2)
Security	HTTPS (SSL), IP filtering, 802.1x, Digest Authentication (ID/PW)
SIP/VoIP Support	N/A
Plug In	CGI API, ONVIF

## I/O & EVENT

Audio In / Out	N/A
Alarm In /Out	N/A
Video Output (2nd Video Out)	1 [CVBS 1.0V p-p (75Ω)], 4:3 aspect ratio
Event Trigger	Motion, Network disconnection, temperature critical
Pre-Post Recording	Pre: 1 ~ 0~5 sec Post: 1~240 sec
Event Notification	FTP, E-Mail, SD Card
Ethernet	RJ45 (10/100BASE-T)

## GENERAL







Support Languages	English, Korean, Japanese
Power	(Adaptor is not Included) DC12V POE IEEE 802.3af Class3
Power Consumption	DC12V Max 7.1W PoE Max 9.2W
Temperature	-20°C ~ 50°C
Humidity	10~90% RH (non-condensing)
Housing	Aluminum Die-casting
Dimensions (D x H)	Ø125 x 92 mm
Weight	0.85kg
Compliance	IP66

## STRUCTURE

Dome	125 Ø
Height	92 mm
Width	125 mm
Length	125 mm
Weight	Net: 0.85kg



**MVP9-A4-R** **ViewPro** 



**Dimensions (mm/inch)**

